(51) International Patent Classification 6 : H04L 25/02	A1	(11) International Publication Number: WO 99/56440
		(43) International Publication Date: 4 November 1999 (04.11.99)

(21) International Application Number: PCT/GB99/01313

(22) International Filing Date: 27 April 1999 (27.04.99)

(30) Priority Data:
98303326.7   28 April 1998 (28.04.98)   EP

(71) Applicant (for all designated States except US): LUCENT TECHNOLOGIES INC. [US/US]; 600 Mountain Avenue, Murray Hill, NJ 07974–0636 (US).

(72) Inventors; and
(75) Inventors/Applicants (for US only): LUSCHI, Carlo [IT/GB]; 15 Sadler Walk, Oxford, Oxfordshire OX1 1TX (GB). SPEIGHT, Timothy, James [GB/GB]; 16 Richmond Terrace, Clifton, Bristol BS8 1AA (GB). YAN, Ran–Hong [–/GB]; Hawthorns, Kings Lane, Longcot, Faringdon, Oxon SN7 7SS (GB).

(74) Agents: WILLIAMS, David, John et al.; Lucent Technologies UK Limited, 5 Mornington Road, Woodford Green, Essex IG8 0TU (GB).

(81) Designated States: AU, BR, CA, CN, JP, KP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
With international search report.

(54) Title: CHANNEL ESTIMATION USING A SLIDING WINDOW TECHNIQUE

(57) Abstract

The invention provides a method for channel estimation in mobile radio communications which adaptively compensates for channel distortion on a block–by–block basis. The discrete–time channel impulse response is initially estimated with a given length and then truncated by using a sliding window. A cost function associated with the window is measured as the length and position of the window is adjusted over the channel impulse response and the cost function is compared with a threshold. The invention provides means to and a method for adaptively adjusting the length of the window L_T and the corresponding number of states in the equalizer, 2^{L_T-1} if appropriate.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

CHANNEL ESTIMATION USING A SLIDING WINDOW TECHNIQUE

This invention relates to channel estimation methods and apparatus in mobile radio communications and in particular to a receiver which adaptively

5   compensates for channel distortion on a block-by-block basis.

In digital mobile radio communications, transmission channels suffer from severe distortion due to frequency selective fading. In addition, channel characteristics are normally time-varying due to the relative motion of fixed and mobile stations. Therefore, in order to allow for reliable transmission, the receiver must be able

10   to estimate and compensate for channel distortion on a block-by-block basis.

Various channel estimation and channel equalization methods have been proposed in literature and are commonly used in practical systems such as mobile cellular communication systems employing the European wireless digital cellular standard "GSM". In most cases the receiver performs channel equalization on the

15   received signal using Maximum Likelihood (ML) or Maximum A Posteriori (MAP) probability data estimation, based on the knowledge of the Channel Impulse Response (CIR). Most practical systems employ training sequences to enable the CIR to be estimated before the equalizer star-up. Fast time varying, fading channels require the changing channel response to be tracked and adjusted dynamically by the receiver for

20   the duration of the received signal. Tracking of the CIR may be performed by means of decision directed algorithms, where tentative decisions from the equalizer are used to update the initial CIR estimate. Examples of receiver systems which perform channel estimation and channel equalization may be found in the following articles: "Bit Synchronisation and Timing Sensitivity in Adaptive Viterbi Equalizers for Narrowband

25   TDMA Digital Mobile Radio Systems", A. Baier, G. Heinrich and U. Wellens, Proc. IEEE Vehicular Technology Conference, June 1988, pp 377-384 [Reference 1]; "Correlative and Iterative Channel Estimation in Adaptive Viterbi Equalizers for TDMA Mobile Radio", ITG-Fachbericht No. 107, VDE Verlag, April 1989, pp 363-368 [Reference 2]; "Simulation and Hardware Implementation of a Viterbi Equalizer for the

30   GSM TDMA Digital Mobile Radio System", A. Baier, G. Heinrich, P. Shoeffel and W.

Stahl, Proc. 3rd Nordic Seminar on Digital Land Mobile Radio Communications, September 1988 pp 13.7.1 - 13.7.5, [Reference 3].

    An equalizer of a given complexity can only cope with a certain delay spread of signal paths. Therefore, the estimated CIR is usually truncated and this

5 truncated CIR estimate is used in a reduced state equalizer, of the type described in "Mobile Radio Communications" by R. Steels, pub. By Rentech Press and IEEE Press, pp 560-575. The reduced state equalizer selects an appropriate segment of the estimated CIR by sliding a window of length L_T over the whole estimated response, calculating the energy contained within the window at each window position and identifying the

10 window position where the energy within the window is maximum.

    However, if the actual CIR is either longer or shorter than L_T samples, the above approach results in a degradation of the equalizer performance. In fact, as it is intuitive, assuming a channel response shorter than required produces a residual ISI which will affect the data estimation. On the other hand, assuming an impulse response

15 longer than necessary means making use of one or more taps of the estimates channel which are essentially noise. There is thus a requirement for a reduced-state equalizer which provides improved equalizer performance.

    According to a first aspect of the invention there is provided a method of estimating channel impulse response in a communication system comprising:

20   initially estimating the discrete-time channel impulse response with a given discrete length; and

          truncating the channel impulse response by using a sliding window, and characterised in that a cost function associated with the window is measured as the length and position of the window is adjusted over the channel impulse response and the

25 said cost function is compared with a threshold.

    The overall performance of the equalizer is improved by neglecting the portion of the estimated CIR which is likely to correspond to just estimation noise.

    The invention provides means to and a method for adaptively adjusting the length of the window L_T and the corresponding number of states in the equalizer,

30 $2^{L_T} - 1$ if appropriate. This may be achieved by computing a cost function for different

lengths and positions of the window, for example by measuring the out-of-window power for each window, and comparing that cost with a suitable threshold.

Once L samples CIR have been obtained by standard means, the position of the truncated CIR of different lengths L_T is then obtained by performing several 5 maximum energy searches based on sliding windows of length L_T. For each window length, the out-of-window energy of the estimated CIR is compared with a suitable threshold. The threshold may be fixed, or it may be obtained from a previous estimate of the SNR (based on the non-truncated channel estimate). The invention may also be implemented by comparing the energy of the individual CIR taps with a suitable 10 threshold. Again, the threshold may be fixed, or it may be obtained from a previous estimate of the SNR (based on the non-truncated channel estimate).

A detailed description of a practical digital radio receiver is described below, by way of example, and with reference to the following figures in which:

Figure 1 shows in outline a typical GSM digital radio receiver;

15   Figure 2 illustrates the GSM "normal" burst format;

Figure 3 illustrates a sliding window;

A typical implementation of a digital radio receiver is shown in Figure 1 and comprises an equalizer 10, deinterleaver 15 and a channel decoder 16. The equalizer includes a channel estimator 11 and data estimator 14. The channel estimator 20 includes an initial channel estimator 12 and a channel truncator 13.

The discrete-time received signal as received by the equalizer can be written as

$$r(k) = \sum_l b(k\text{-}l)\, h(l) + n\,(k) \qquad\qquad (1)$$

where $b(k) \in \{-1,1\}$ are the transmitted data symbols or the (known) training sequence 25 symbols, $h(l)$ $l = 1, 2, ..., L$ represents the taps of the Channel Impulse Response (CIR) and $n(k)$ indicates white Gaussian noise with zero mean and variance σ^2.

The equalizer must first estimate (12) the CIR $\hat{h}(l)$, before beginning the data estimation process (14). In some cases, e.g. in a GSM standard receiver, the initial CIR estimation is commonly performed by means of correlative channel sounding, see 30 for example the above mentioned references 1 and 3. The taps of the CIR estimate are

obtained by correlating the received signal $r(k)$ with N=16 bits $b(k)$ out of the 26 bits of training sequence, shown in figure 2, and represented by:

$$\hat{h}(l) = (1/N)\sum_{i}b(i)r(l+i) \qquad (2)$$

where

5          $i = 0, 1, \ldots N-1;$

The initial CIR estimate can generally be performed by ML channel estimation, giving:

$$\hat{h} = [\hat{h}(0),\hat{h}(1),...,\hat{h}(L-1)]^T = (\mathbf{B}'\mathbf{B})^{-1}\mathbf{B}^T\mathbf{r} \qquad (3)$$

where

10         $\mathbf{r} = [r(0),r(1),...,r(N-1)]^T$

$\mathbf{B} = [\mathbf{b}(0),\mathbf{b}(1),...\mathbf{b}(N-1)]^T$

$\mathbf{b}(i) = [b(i),b(i-1),...,b(i-L+1)]^T$

It can be seen that, due to the good autocorrelation properties of the GSM training sequence $\mathbf{B}'\mathbf{B} \cong N\mathbf{I}$ and equation 2 is the particular case of the more general

15 ML technique (equation 3). Once L samples ($\hat{h}(l)$) of the CIR are estimated, an appropriate segment of samples ($\hat{h}_T(l)$ for $L_T < L$) is selected (in the channel truncator 13) by a maximum energy search based on a sliding window at length L_T, see reference 1, and as shown in figure 3. This approach produces a bit synchronisation with a resolution equal to the sampling period T and results in a reduced complexity equalizer

20 with a trellis of 2^{L_T-1} states.

Assuming that for the training sequence bits b(k)

$$R_{bb}(k) = \sum_{i}b(i)b(k+i) = N\delta_{k,0}, \qquad (4)$$

substituting (1) in (2) yields

$$\hat{h}(l) = h(l) + v(l), \qquad l=0,1,...,L-1. \qquad (5)$$

25 where

$$v(l) = \frac{1}{N}\sum_{i=0}^{N-1}b(i)n(l+i) \qquad i=0,1,...N-1, \qquad (6)$$

Suppose that L_T taps of $\hat{h}(l)$ are selected as a CIR estimate $\hat{h}_T(l)$, when the actual channel response is shorter than L_T bit intervals. From (5), it is clear that if

$h(l) = 0$ for some index l, the corresponding sample $\hat{h}_T(l)$ is just noise, and its use can only degrade the equaliser performance. An improvement may be achieved by adaptively adjusting the parameter L_T on a block-by-block basis, and consequently adjusting the number of states 2^{L_r-1} of the equaliser, in order to match the actual length of the channel impulse response.

A suitable cost function, such as the square error of the truncated channel estimate, may be used to estimate length of the actual CIR and is given by:

$$J(l_0, L_T) = \sum_{l=0}^{L-1} |h(l) - \hat{h}_T(l)|^2 \qquad (7)$$

where $\hat{h}_T(l) = \hat{h}(l)$ for $l \in W = [l_0, l_0 + L_r - 1]$, and $\hat{h}_T(l) = 0$ for $l \notin W$. Taking into account (5), the above quantity can be written as:

$$J(l_0, L_T) = \sum_{l \in W} |v(l)|^2 + \sum_{l \notin W} |h(l)|^2 \qquad (8)$$

Therefore, choosing the value of (l_0, L_T) which minimise the cost (7) implies a trade-off between reducing the estimation noise and representing the relevant ISI terms. From (5) and (8), and assuming $\sum_{l \in W} h(l)v^*(l) \approx 0$, the following equation is finally obtained:

$$J(l_0, L_T) = 2\sum_{l \in W} |v(l)|^2 + \sum_{l \notin W} |\hat{h}(l)|^2 \qquad (9)$$

However, in comparing the cost associated with different window lengths L_T, the above approach requires an accurate estimate of the squared value of the estimation error $v(k)$ as defined in (6). From this, as an alternative to (9), one can consider the following process. Assume that, for each window length L_T, the best window position l_0 is determined by a maximum energy search. Once a value of l_0 is associated with each length L_T, the best L_T can be chosen by comparing the out-of-window energy $\sum_{l \notin W} |\hat{h}(l)|^2$ corresponding to the different values of L_T with a suitable threshold. In the case where the out-of-window taps of the estimated channel do not contain any

relevant ISI terms, using (5) and (6) and by denoting with E_L and E_{LT} the energy of

$\hat{h}(l)$ and $\bar{h}_T(l)$ respectively, for signal-to-noise ratios $(\sum_{l=0}^{L-1}|h(l)|^2)/\sigma^2 > \gamma$

one has

$$E_L - E_{LT} = (L - L_T)(\sigma^2/N) < (L - L_T)(E_{LT}/\gamma N). \tag{10}$$

5   Therefore, for each burst, the quantity E_L-E_{LT} is computed and the validity
of (10) is checked for different values of L_T. The lowest L_T satisfying the
inequality (10) is an estimate of the length of the actual channel response,
and may be then used both as a length of the CIR and for setting the
number of states in the equaliser.

10   The effectiveness of the invention has been asses by computer simulation
for the case of a GSM receiver. The GMSK transmitted data symbols are obtained
from the source bits by a rate 1:2 convolutionally encoding and interleaving , according
to the GSM specifications for the TCH/FS class Ib bits.   At the receiver, the channel
estimation is performed by using N=16 bits out of the 26-bits training sequence
15   midamble of the GSM normal burst, according to (2). The original $\bar{L}$ = 8 taps estimate
are then truncated to $L_T \leq 6$ samples according to the rule (9) or (10). For data
estimation, we employ a symbol-by-symbol Max-Log-MAP equalizer on the ISI trellis
with state complexity 2^{L_T-1}. The equalizer soft-output data are deinterleaved and then
fed to a symbol-by-symbol-Max-Log-MAP convolution channel decoder.

20   Two channel profiles from "Digital cellular telecommunications system
(phase 2+): Radio transmission and reception." ETSI GSM 05.05 (version 5.2.0), July
1996 are considered. The first is the GSM typical urban area profile (TU50) with a
relative speed of 50 Km/h and a delay spread of about 5μsec. The second propagation
condition is the GSM typically hilly terrain profile (HT100), with a relative speed of
25   100Km/h and a delay spread of about 20μsec. Considering the GSM symbol interval T
= 3.69 μsec, and taking into account that the GSMK pulse duration is about 3T, the
above propagation conditions correspond to the two opposite cases where the invention
provides a significant (TU conditions) and a negligible (HT conditions) performance
improvement respectively.

To measure the performance of the different channel estimation algorithms, the means square error between the true and estimated channel responses are considered. In the case of the TU50 conditions, both strategies (9) and (10 produce a gain at the equalizer output and at the channel decoder output. For the HT100 profile,

5 no significant improvement is achieved and the BER is similar to a conventional receiver.

Claims

1.   A   method   of   estimating   channel   impulse   response   in   a communication system comprising:

initially estimating the discrete-time channel impulse response with a given length; and

truncating the channel impulse response by using a sliding window, and characterised in that a cost function associated with the window is measured as the length and position of the window is adjusted over the channel impulse response and the said cost function is compared with a threshold.

2. A method as claimed in claim 1 characterised in that the cost function is computed for each different length and/or position of the window.

3. A method as claimed in claim 1 characterised in that the out-of-window power is used as the cost function.

4. A method as claimed in claim 1 characterised in that the length and position of the window given the best result, when compared with the threshold, is chosen as the channel impulse response estimate.

# Fig.1.

Fig.2.

TAIL BITS	DATA BITS	TRAINING SEQUENCE	DATA BITS	TAIL BITS	GUARD PERIOD
3	58	26	58	3	8.25

Fig.3.

INTERNATIONAL SEARCH REPORT

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6   H04L25/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6   H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical. search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category '	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 496 152 A (ROKE MANOR RESEARCH) 29 July 1992 (1992-07-29) abstract column 3, line 18 - column 5, line 28 ---	1-4
A	EP 0 829 988 A (NOKIA TECHNOLOGY GMBH) 18 March 1998 (1998-03-18) column 7, line 16 - column 8, line 12 --- -/--	1-4

[X] Further documents are listed in the continuation of box C.   [X] Patent family members are listed in annex.

' Special categories of cited documents :

"A" document defining the general state of the art which is not
     considered to be of particular relevance
"E" earlier document but published on or after the international
     filing date
"L" document which may throw doubts on priority claim(s) or
     which is cited to establish the publication date of another
     citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or
     other means
"P" document published prior to the international filing date but
     later than the priority date claimed

"T" later document published after the international filing date
     or priority date and not in conflict with the application but
     cited to understand the principle or theory underlying the
     invention
"X" document of particular relevance; the claimed invention
     cannot be considered novel or cannot be considered to
     involve an inventive step when the document is taken alone
"Y" document of particular relevance: the claimed invention
     cannot be considered to involve an inventive step when the
     document is combined with one or more other such docu-
     ments, such combination being obvious to a person skilled
     in the art.
"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
13 July 1999	20/07/1999

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040. Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Koukourlis, S

1

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category '	Citation of document. with indication.where appropriate. of the relevant passages	Relevant to claim No. -._
A	BAIER A ET AL: "Bit synchronization and timing sensitivity in adaptive Viterbi equalizers for narrowband-TDMA digital mobile radio systems" 38TH IEEE VEHICULAR TECHNOLOGY CONFERENCE: 'TELECOMMUNICATIONS FREEDOM - TECHNOLOGY ON THE MOVE' (CAT. NO.88CH2622-9), PHILADELPHIA, PA, USA, 15-17 JUNE 1988, pages 377-384, XP002077506 1988, New York, NY, USA, IEEE, USA cited in the application ---	1-4
A	WO 90 13187 A (ERICSSON TELEFON AB L M) 1 November 1990 (1990-11-01) abstract page 26 - page 27 -----	1-4

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0496152	A	29-07-1992	GB 2252221 A		29-07-1992
			AT 146922 T		15-01-1997
			DE 69123830 D		06-02-1997
			DE 69123830 T		12-06-1997
			DK 496152 T		09-06-1997
			ES 2095300 T		16-02-1997
EP 0829988	A	18-03-1998	FI 963649 A		17-03-1998
WO 9013187	A	01-11-1990	US 5042082 A		20-08-1991
			AU 625128 B		02-07-1992
			AU 5530090 A		16-11-1990
			CA 2030607 A		18-10-1990
			KR 9513303 B		02-11-1995
			US 5257401 A		26-10-1993
			AU 626123 B		23-07-1992
			AU 5934090 A		17-01-1991
			AU 625085 B		02-07-1992
			AU 5969890 A		17-01-1991
			CA 2033340 A		27-12-1990
			CA 2033971 A		27-12-1990
			CN 1048472 A,B		09-01-1991
			DE 69021794 D		28-09-1995
			DE 69021794 T		22-02-1996
			DE 69022307 D		19-10-1995
			DE 69022307 T		08-02-1996
			EP 0406186 A		02-01-1991
			EP 0406193 A		02-01-1991
			HK 173995 A		24-11-1995
			HK 180295 A		01-12-1995
			JP 2799244 B		17-09-1998
			JP 4500446 T		23-01-1992
			JP 2799245 B		17-09-1998
			JP 4500448 T		23-01-1992
			KR 9702756 B		10-03-1997
			KR 9709704 B		17-06-1997
			PH 26898 A		03-12-1992
			WO 9100657 A		10-01-1991
			WO 9100658 A		10-01-1991
			US 5008953 A		16-04-1991
			US 5200957 A		06-04-1993